

< >

# 가

( ) 91 1 6760 6000 38.5% 가 ,  
 6871 6000 5.9%  
 90 7299 8000 60.3% 91 6871 6000  
 40.9% ,  
 91 1999 1000 3.1% ,  
 1572 2000 6.0% 가 .  
 HDPE 957 2000 4.7% 가 , SM 659 9000 23.9%, M-C4 392  
 4000 48.0%

< 1>

( : , %)

	1988	1989	1990	1991
가	7764.7	8917.4	12100.3	16760.6
	48.1	14.8	35.6	38.5
	1283.2	1130.1	1282.1	1552.2
	920.8	746.0	801.2	890.3
	291.2	301.0	412.8	309.5
가	84.2	112.1	101.9	882.7
	25.7	33.0	9.0	13.4
	6721.1	7777.7	9629.6	13387.4
	4472.6	4804.8	4434.9	4322.6
	12605.0	14820.4	16552.3	21023.7
	3859.8	4930.5	6368.6	8989.3
	5192.3	5708.5	6058.6	7883.7
	9052.1	10714.1	12483.5	16910.6
	652.2	975.0	975.0	990.1
	3552.8	4106.2	4068.7	4113.0

< 2>

( : , , %)

	1990		1991			1992( )		
	735,969	2064.0	703,288	1999.1	3.1	595,000	1680.0	16.0
	424,723	1483.3	407,195	1572.2	6.0	340,000	1350.0	14.1
	170,176	181.5	156,850	128.8	29.0	153,000	125.0	3.0
	66,786	183.8	63,836	144.4	21.4	93,500	210.0	45.4
	56,190	137.5	39,326	88.2	35.9	51,000	115.0	30.4
	1,453,844	4050.1	1,370,495	3932.7	2.9	1,232,000	3480.0	11.5
H D P E	155,016	914.4	173,101	957.2	4.7	170,000	955.0	0.2
S M	135,603	867.2	135,752	659.9	23.9	120,000	565.0	14.4
MixedC4	310,473	754.6	247,621	392.4	48.0	221,000	350.0	10.8
M T B E			60,000	146.0		90,000	220.0	50.7
	446,076	1621.8	443,373	1198.3	26.1	601,000	1135.0	5.3
		713.5		783.4	9.8		630.0	19.6
		7299.8		6871.6	5.9		6200.0	9.8
		4800.5		9889.0	106.0			
		12100.3		16760.6	38.5			

) , 가

9 2000

MTBE 6 146

4 가 가 가

11 , 가  
 NCC 가 73% , 가

4 100% 가

가 85%

5800 6000

92 6000

17.8%

60 , 40

34

16.0%,

14.1%