

< >

36%

() 91 5079 17.2% 가 ,
58 9000 7.6% 가 .
ABS · PS 가 ,
697 5000 48.7% 가 .
가 . EPS 가
가 1400 6000 27.6%, 3678 4000 72.4%

< 1>

	1988	1989	1990	1991
가	2222.0 19.6	3037.4 36.6	4331.0 42.5	5079.0 17.2
	605.7 203.6 85.3	903.9 336.8 107.9	1160.1 469.2 44.8	1553.8 697.5 80.7
가	59.2 58.0	57.4 3.0	54.7 4.7	58.9 7.6
	1550.2 1549.5 3651.1	2383.8 2367.7 5474.4	3186.3 2736.9 6764.6	3385.9 4542.8 9172.6
	1729.9 1278.0 3031.6	2382.9 2219.6 4619.1	3222.5 2507.9 5740.0	4157.4 2524.7 6685.6
	220.0 619.4	300.0 855.2	360.0 1024.5	360.0 2486.9

< 2>

(: , , %)

			1990		1991			1992()		
A	B	S	30,973	385.5	44,961	539.7	40.0	56,822	697.0	29.1
P		S	80,013	711.2	95,867	783.6	10.2	110,870	827.0	5.5
S	A	N	—	—	3,386	29.0	—	19,568	163.0	462.0
E	P	S	—	—	—	—	—	17,000	151.0	—
			1,528	28.8	2,124	48.3	67.7	2,760	62.0	28.3
			112,514	1125.5	146,338	1400.6	24.4	207,020	1900.0	35.7
	(YDS/LBS)		16,368,000	1761.3	15,792,000	1789.4	1.6	—		
	()		2,632,000	1351.2	3,604,000	1761.3	30.4	—	4193.0	14.0
	(m ²)		405,000	93.0	452,000	127.7	37.3	—		
			—	3205.5	—	3678.4	14.8	—	4193.0	14.0
			—	4331.0	—	5079.0	17.2	—	6093.0	20.0

91 PS 783 6000 (15.4%) 10.2% 가 ,
ABS 539 7000 (10.6%) 40.0% 가 . SAN 3386 , 29

ABS 13 2067 2 6745 20.2%
, PS 41 1261 5 1172 , 12.4%
PS , ABS

92 6093 20.0%, 1900
35.7% 가

가 91 27.6% 31.2%
, ABS 가 697 29.1% 가 EPS(3)
가 , 1 7000 151
SAN , 1 9568 163
EMC, PMMA,

가

.

< 1992/6/1>