SM

SM 가

가 SM 94

가 가

가

SM (: 1000M/T)									
		19	94	19	95	1996			
			SM	SM			SM		
	PS	150	108	150	108	150	108		
	EPS	70	60	70	60	70	60		
	ABS	80	43	150	43	150	81		
	SAN	40	29	40	29	40	29		
		340	240	410	240	410	278		
LG	PS	100	90	100	90	100	90		
	EPS	40	30	40	30	40	30		
	ABS	145	87	145	87	145	87		
	SAN	40	32	40	32	40	32		
·		325	239	325	239	325	239		
	PS	120	92	120	92	120	92		
	EPS	35	30	35	30	35	30		
	ABS	60	32	120	65	120	65		
	SAN	40	29	80	58	80	58		
		255	183	355	244	355	244		
BASF	PS	100	91	150	123	170	155		
	EPS	60	58	60	58	60	58		
	ABS	35	21	35	21	85	38		
		195	170	245	202	315	251		
	PS	90	72	90	72	90	72		
	EPS	45	38	45	38	45	38		
		135	110	135	110	135	110		
	PS	20	9	20	15	20	18		
	EPS	40	30	40	30	40	35		
	ABS	35	15	35	15	35	20		
		95	54	95	60	95	73		
	PS	580	462	630	500	650	535		
	EPS	290	246	230	246	290	255		
	ABS	355	198	485	231	535	292		
	SAN	120	90	160	119	160	119		
		1,345	996	1,505	1,096	1,635	1,201		

LG

130 , 15 11 , 36 SM 94 30 , 96 8 96 1 95 30 가 가 95 135 , 96 93 125 94 SM 130 170 , 94 15 95 19 가 93 14 96 가 93 90 , 94 110 95 120 , 96 135 10%

	SM				(: 1000M/T,)
		120	-	-	1986.6	BADGER ENG'G
		110	-	-		MONSANTO/LUMMUS
		100	-	350	1989.12	MONSANTO/LUMMUS
L G	i	120	-	800	1990.5	LUMMUS/MONSANTO
L G	;	180	-	600	1991.12	LUMMUS/MONSANTO
L G	i	30	-	-	1993.12	
		240	-	-	1991.5	BADGER
		-	300	800	1996.1	
		253	-	3,000	1991.1	BADGER/MOBIL/ARCO
		50	-	-	1994.10	
		125	-	-	1991.10	BADGER
		-	300	-	1996.8	
		1,328	600			

174 140 19.5 150 7.1 190 26.6 180 1,388 1,390 1.4 1,450 4.3 1,540 6.2 1,880	SM (: 1000M/T, %										Γ, %)
174 140 19.5 150 7.1 190 26.6 180 1,388 1,390 1.4 1,450 4.3 1,540 6.2 1,880			1992	1993		1994		1995		1996	
174 140 19.5 150 7.1 190 26.6 180 1,388 1,390 1.4 1,450 4.3 1,540 6.2 1,880											
1,388 1,390 1.4 1,450 4.3 1,540 6.2 1,880			1,214	1,250	2.9	1,300	4.0	1,350	3.8	1,700	25
7.22 7.22 7.22			174	140	19.5	150	7.1	190	26.6	180	5
860 900 4.6 1.100 22.2 1.200 9.1 1.350			1,388	1,390	1.4	1,450	4.3	1,540	6.2	1,880	22
			860	900	4.6	1,100	22.2	1,200	9.1	1,350	12
423 400 5.4 360 10.0 340 5.6 520			423	400	5.4	360	10.0	340	5.6	520	52
1,283 1,300 1.3 1,460 12.3 1,540 5.5 1,870			1,283	1,300	1.3	1,460	12.3	1,540	5.5	1,870	21

93 40 96 52 94 36 , 95 34 21 , 11 20 가 4 , 5 10 12 5 LG 32 가 30 , 24 12 96 30 54 30 24 60 ~ 80% 95 10% PS 46 SM 94 · , 가가 PS/ABS 가 26 23.6%, ABS 20 18.2%, 94 42.0%, EPS SAN 가 9 8.1% 94 가 PS 10 8000 , EPS 6 , ABS , 94 4 3000 , SAN 2 9000 24 8 15 96 SM 가 95 ABS 28

LG 94 PS 9 , EPS 3 , ABS 8 7000 , SAN 3 24 SM 가 . LG PS ABS 가

.

() (: M/T) SM 90,000 (8.1%) SAN 90,000 PS (8.1%) 460,000 ABS (42.0%) 200,000 (18.2%) EPS 260,000 (23.6%)

가 94 95 SM 가 95 4 FOB Korea 1440 5 1300 , 7 950 , 9 500 , 10 470

< 96 >