

...95 11 31 9000

95 가 11

96 1 1

가

(1995.1～10)												
(: 1000M/T, %)												
()												
	1994	1995		1994	1995		1994	1995		1994	1995	
	3,012.0	3,058.2	1.5	-	55.0	-	319.0	255.6	19.9	2,693.0	2,857.6	6.1
	1,728.1	1,760.6	1.9	55.6	97.7	75.8	88.4	115.1	30.2	1,695.2	1,743.2	2.8
	452.7	475.7	5.1	-	1.0	-	213.5	198.9	6.8	239.1	277.8	16.2
	4,851.0	5,040.4	3.9	110.6	98.4	11.1	1,917.0	2,117.9	10.5	3,044.7	3,020.8	0.8
	1,759.5	2,127.4	20.9	834.4	894.2	7.2	72.2	256.7	255.4	2,521.7	2,764.9	9.6
	213.8	218.5	2.2	35.1	22.4	36.2	92.2	68.4	25.8	156.7	172.6	10.1
3	6,824.4	7,386.3	8.2	980.1	1,015.0	3.6	2,081.4	2,443.0	17.4	5,723.1	5,958.3	4.1

, 95 11 31 9000 32 0.4%

10 28 59000 11.6%

20 2600 , 18 5900 , 16 5400 9.0%, 22.5%

가

4 7800 4 8500 1.5% 4 7300

1.0% 가,

, , 3 78 3800 71 7000 9.3%,

75 3900 4.0%

22 5900 , 17 6100 , 20 4900 28.3%,

10.2% 가

53 4200 51 8300 , 52 5200 3.1%, 1.7%

가

2 2600 4.5% 가 , 2 3800 0.6%

2 3700 가 가 , NCC 95 10 86% 11

90% 4%P 가 85% 90% 5%P

31 3800 , 30 6600 2.5%, 0.2%

30 6000 24 7000 20 8000 , 23 1700

23.0%, 6.6% 가

27.4%, 14.4% 가

54.5% 73.5%

가가

