

MEK

6 80% ...

MEK Tonen, Mamzen, Idemitsu 3 80%
Shell Celanese , 3
가
92 7 Shell , 93 3/4 Shell 93
TASCO 3 가
Shell 1300 1100

MEK (: 1000M/T, %)										
	91	85~91	92	93	94	95	96	97	98	92~98
	0.00	0.00	0.00	0.00	0.00	50.00	50.00	50.00	50.00	
	54	19	59	61	67	21	25	31	36	8
()	7.9		12	12	12	53	27	23	20	
	0.005	400	0.005	0.005	0.005	0.000	0.000	0.000	0.000	0.00
()	96		0.00	0.00	0.00	0.00	0.00	0.00	0.00	
	54	19	60	62	67	71	76	80	87	7
()	7		7	7	7	7	7	7	7	

MEK (: M/T)						
		88	89	90	91	92
		280	0	-	102	650
		240	100	-	-	1,200
		240	260	103	320	350
		760	360	103	432	2,200
		5,400	3,000	2,800	4,900	6,500
		425	-	-	480	-
		190	100	-	-	400
		2,490	900	1,498	1,400	1,450
		3,800	3,310	7,700	4,550	4,000
		1,100	200	300	790	1,500
		941	62	104	62	2,300
		180	-	-	-	-
		129	-	154	-	700
		3,789	2,940	1,780	6,000	6,000
		70	-	-	-	-
		-	-	-	250	3,000
		45	-	-	-	-
		117	-	240	770	1,700
		-	-	200	75	-
		-	-	-	100	-
		-	-	-	100	500
		-	-	100	100	600
		18,676	10,512	14,876	19,577	28,650
TAPE		764	194	116	1,010	1,200
	SKM	1,893	2,555	2,059	4,267	6,500
	SKC	0	1,900	2,938	2,152	1,400
		674	2,160	3,188	2,805	2,800
	SKI	-	-	-	-	400
		1,156	2,342	957	3,076	5,000
		52	-	-	-	-
		-	-	-	399	-
		-	402	346	-	-
		1,208	2,744	1,303	4,105	5,000
		1,126	770	376	-	1,500
		442	52	-	-	500
		179	-	-	-	-
		-	-	969	1,006	2,800
		-	-	-	103	-
		82	-	-	-	-
		-	-	-	-	300
		1,829	822	1,345	1,109	5,100
		22,473	14,438	17,627	25,223	40,950

MEK 89 4 5000 , 90 6 , 91 6 5000 , 92 6 .
 90 91 Celanese . 92
 日本 4 2000 (70%), Shell 14000 (23%), Celanese 4200 (7%) Condea 2000 (3%)
 93 가 1/4 520 5 510 6
 8 가
 92 6 end-user 3 , Dealer가 3 Video
 20%, 18%, 13%, 7%, PVC 8%, 13%, 21%
 Volatile Compound Solvent
 VOC (Volatile Organic Com-pound Regulation)
 Solvent High Solids, Solventless, UV -
 Curable, Water-Borne Solvent , Low Solid High Solvent 95
 44% 26% . 88
 Blend(MEK · MIBK · Aceton · Ethyl · Propionate) Solvent . 89
 가 MEK 가 Solvent MEK
 9000 . Solvent Recovery System
 MEK
 5 ~ 10%
 92 MEK 70 ~ 80
 가 가