

, 가

가 94 4/4 (95 1 3) 가 87 8000 1.6% , 1.9% 가

102 6300 1.6% , 1.8% 가가

(: 1000M/T)				
	1994.2/4	1994.3/4	1994.4/4	
P V C	48.1	49.3	47.7	3.9
	270.0	285.0	247.0	1.8
	6.8	8.0	7.5	8.5
	54.6	64.5	59.1	10.0
P O	62.1	63.1	69.6	-
	53.6	61.6	62.9	4.1
	67.2	70.5	69.5	10.1
	40.0	43.0	43.0	1.8
T D I · M D I	103.3	101.5	99.0	4.2
	294.3	296.0	294.0	2.2
	1,000.0	1,042.5	1,026.3	1.8
	185.4	185.0	185.0	0.9
가	814.6	857.5	841.3	2.4
	932.5	980.0	961.0	2.4

가 (: 1000M/T)				
	1994.2/4	1994.3/4	1994.4/4	
	31.2	30.4	30.4	5.6
	96.9	99.2	97.9	3.9
	5.1	5.2	5.3	-
	15.9	16.3	15.8	7.1
	20.6	21.0	21.0	6.2
	17.5	20.5	16.0	1.9
	27.0	25.0	26.0	2.4
	130.3	135.2	130.1	2.7
	18.9	19.5	19.0	0.5
	34.9	36.0	36.0	2.9
	248.1	261.6	269.7	0.7
	476.7	497.8	496.8	1.5
	6.3	8.0	7.5	5.1
	8.2	8.5	8.0	2.6
	187.8	205.6	195.3	5.3
	848.7	892.0	878.0	1.9

PVC 27 4000 1.8% 가 , PO, TDI · MDI 가

가 3/4 85 7700 84 1300 , 4/4 2.4% 가가

